

96% AFUE GAS FURNACES



All gas furnaces feature SmartLite® Control Boards



iQ Drive READY

FG7T(E, N)-VS

96% AFUE Ultra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Dedicated Upflow, Downflow), iQ Drive ready, 60,000 - 120,000 BTUH Input, Variable-Speed ECM Blower Motor



FG7T(E, N)-FS

96% AFUE Ultra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Dedicated Upflow, Downflow), Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input



95.1% AFUE GAS FURNACES



iQ Drive READY

FG7TC-VS

95.1% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage Upflow/Horizontal, iQ Drive Ready, 60,000 - 120,000 BTUH Input, Variable-Speed ECM Blower Motor



95% AFUE GAS FURNACES

FG7S(D, M)

95% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow), Multi-Speed ECM Blower Motor, (38,000 - 120,000, 54,000 - 90,000) BTUH Input



92.1% AFUE GAS FURNACES

FG7S(C, L)

92.1% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow), Multi-Speed ECM Blower Motor, (38,000 - 120,000, 72,000) BTUH Input



80% AFUE GAS FURNACES

FG7T(A, K)-VS

80% AFUE Mid Efficiency, 2-Stage (Upflow/Horizontal, Downflow), iQ Drive Ready, 60,000 - 120,000 BTUH Input, Variable-Speed ECM Blower Motor



FG7S(A, K)-FS

80% AFUE Standard Efficiency, 1-Stage (Upflow/Horizontal, Downflow), Multi-Speed ECM Blower Motor, (45,000 - 126,000, 54,000 - 126,000) BTUH Input



96% AFUE GAS FURNACES



KG7T(E, N)-FS

96% AFUE Ultra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage (Dedicated Upflow, Downflow), Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input



95.1% AFUE GAS FURNACES



KG7TC-FS

95.1% AFUE Extra High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 2-Stage Upflow/Horizontal, Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input



95% AFUE GAS FURNACES

KG7S(D, M)

95% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow), Multi-Speed ECM Blower Motor, (38,000 - 120,000, 54,000 - 90,000) BTUH Input



92.1% AFUE GAS FURNACES

KG7S(C, L)

92.1% AFUE High Efficiency, Direct Vent or Non-Direct Vent, Condensing, 1-Stage (Upflow/Horizontal, Downflow), Multi-Speed ECM Blower Motor, (38,000 - 120,000, 72,000) BTUH Input



80% AFUE GAS FURNACES

KG7T(A, K)-FS

80% AFUE Mid Efficiency, 2-Stage (Upflow/Horizontal, Downflow), Multi-Speed ECM Blower Motor, 60,000 - 120,000 BTUH Input



KG7S(A, K)

80% AFUE Standard Efficiency, 1-Stage (Upflow/Horizontal, Downflow), Multi-Speed ECM Blower Motor, (45,000 - 126,000, 54,000 - 126,000) BTUH Input



CONVERTIBLE AIRFLOW PACKAGED SYSTEMS

All gas/electric and iHybrid® packaged systems feature SmartLite Control Boards

All packaged systems feature enhanced coil technology



iQ Drive



R6GI

Ultra High Efficiency, Gas/Electric, iQ Drive® Technology, functions with 2-Stage Gas Heat/5-Stage Cooling output from 2-Stage thermostat, Variable-Speed ECM Blower, Square Duct Connections, Convertible Airflow, 20 SEER, 81% AFUE, Up to 13 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input



R6GF

Gas/Electric, 2-Stage Heat & Cool, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 81% AFUE, 12 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input



DF6SF

iHybrid Dual Fuel, 2-Stage Gas Heat/2-Stage Cooling, Variable-Speed Blower, Square Duct Connections, Convertible Airflow, 15 SEER, 81% AFUE, 8.0 HSPF, 12 EER, 2 - 5 Ton, 80,000 - 120,000 BTUH Input



iHybrid



R8HE

Gas/Electric, 2-Stage Heat, Square Duct Connections, Convertible Airflow, 14 SEER, 95% AFUE, up to 12 EER, 2 - 5 Ton, 60,000 - 96,000 BTUH Input



R8GE

Gas/Electric, Square Duct Connections, Convertible Airflow, 14 SEER, 81% AFUE, 11 EER, 2 - 5 Ton, 45,000 - 120,000 BTUH Input



CONVERTIBLE AIRFLOW PACKAGED SYSTEMS continued

P8SE

Air Conditioner, Square Duct Connections, Convertible Airflow, 14 SEER, up to 11.5 EER, 3 - 5 Ton



Q8SF

Heat Pump, 2-Stage, Hot Gas Defrost, Square Duct Connections, Convertible Airflow, 16 SEER, 8.2 HSPF, 12 EER, 2 - 5 Ton

Q6SE

Heat Pump, Square Duct Connections, Convertible Airflow, 14 SEER/8.0 HSPF, 11 EER, 3 - 5 Ton

HORIZONTAL AIRFLOW PACKAGED SYSTEMS

P7RF

Air Conditioner, 2-Stage Cooling, 5 speed ECM Blower, Round Duct Connections, 16 SEER, 12 EER, 2 - 5 Ton



Q7RF

Heat Pump, Patented Hot Gas Bypass Defrost Technology, 2-Stage Heating and Cooling, 5 Speed ECM Blower, Round Duct Connections, 16 SEER, 8.2 HSPF, 12 EER, 2 - 5 Ton



P7RE

Air Conditioner, Round Duct Connections, 14 SEER, 11 EER, 1-1/2 - 5 Ton

Q7RE

Heat Pump, Round Duct Connections, 14 SEER/8.0 HSPF, 11 EER, 2 - 5 Ton



ENERGY STAR® certification is awarded to products designed to reduce energy consumption and utility costs.

To qualify, packaged systems must have a Seasonal Energy Efficiency Ratio (SEER) rating of 15.0 or higher and an Energy Efficiency Ratio (EER) of 12.0 or higher. Packaged heat pumps must also have a Heating Seasonal Performance Factor (HSPF) of 8.2 or higher.

Gas furnaces must have an AFUE of 95% or higher for northern states, at least 90% AFUE for southern states, have an approved energy efficient blower motor and cabinet air leakage of less than or equal to 2%.

Split system air conditioners and heat pumps must have a 15.0 SEER rating or higher and an EER of 12.5 or higher. Split system heat pumps must also have an HSPF of 8.5 or higher.



BROAN UNITS OFFER A 10-YEAR LIMITED WARRANTY ON ALL PARTS WHEN REGISTERED. PLUS THE BROAN QUALITY PLEDGE ON SELECT MODELS, WHICH STATES IF WITHIN THE FIRST 10 YEARS THE COMPRESSOR OR FURNACE HEAT EXCHANGER FAILS BROAN WILL REPLACE THE ENTIRE UNIT, REGISTRATION REQUIRED. ESA/ESH MODELS CARRY A 1-YEAR QUALITY PLEDGE WHEN REGISTERED. AIR HANDLERS AND COILS CARRY A 3-YEAR ALL PARTS LIMITED WARRANTY AND WHEN INSTALLED WITH A MATCHED OUTDOOR UNIT, WILL CARRY THE OUTDOOR SYSTEM WARRANTY. SEE WARRANTY FOR DETAILS.



SPLIT SYSTEM AIR CONDITIONERS

FSA1BG
Ultra High Efficiency, 20 SEER, iQ Drive® Technology, 2 - 5 Ton Capacity



FSA1BF
Extra High Efficiency, Up to 16 SEER, 2-Stage, 2 - 5 Ton Capacity



ESA1BF
Extra High Efficiency, Up to 16 SEER, 1-Stage, 2, 2-1/2, 3, 3-1/2, 4 and 5 Ton Capacity



FSA1BE/ESA1BE
Extra High Efficiency, Up to 15 SEER, 1-1/2 - 5 Ton Capacity



FSA1BD/ESA1BD
High Efficiency, Up to 14 SEER, 1-1/2 - 5 Ton Capacity



SPLIT SYSTEM HEAT PUMPS

FSH1BG
Ultra High Efficiency, Up to 19 SEER, 10.0 HSPF, iQ Drive Technology, 2 - 5 Ton Capacity



FSH1BF
Extra High Efficiency, Up to 16 SEER, 9.0 HSPF, 2-Stage, 2 - 5 Ton Capacity



ESH1BF
Extra High Efficiency, Up to 16 SEER, 1-Stage, 2, 2-1/2, 3, 3-1/2, 4 and 5 Ton Capacity



FSH1BE/ESH1BE
High Efficiency, Up to 15 SEER, 8.5 HSPF, 1-1/2 - 5 Ton Capacity



AIR HANDLERS

B6VMAX
Multi-Poised, Vertical/Horizontal, Variable-Speed, TXV



B6VMMX
ECM Variable-Speed Motor, Multi-Poised, TXV



B6BMMX
Multi-Poised, Vertical/Horizontal, Multi-Speed, TXV



B6BMMO
Multi-Poised, Multi-Speed



AIR HANDLERS

B6EMMX
ECM Fixed-Speed Motor, Multi-Poised, TXV



B6BW
Vertical Wall Mount



B6EW
Vertical Wall Mount, Multi-Speed, ECM Motor, TXV



MB7VM
Modular Variable-Speed Model (matched with a cased coil easily creates a 2 piece Air Handler)

INDOOR COILS

C7BAM0
A, B, C and D sizes available in various capacities



C7BHMO
A, B, C and D sizes available in various capacities Cased & Vertical/Horizontal, Multi-poised versions available



C7BAMX
Factory-installed TXV A, B, C and D sizes available in various capacities



C7BHMx
Factory-installed TXV A, B, C and D sizes available in various capacities Cased & Vertical/Horizontal, Multi-poised versions available



C6BH-X
A, B, C and D sizes available in various capacities Cased Horizontal



Specifications and illustrations subject to change without incurring obligation.



broanhvac.net
Broan® trademark used under license. iHybrid®, iQ Drive®, ecoLogic® and SmartLite® are registered trademarks of Nortek Global HVAC, LLC. © Nortek Global HVAC, LLC 2019. All Rights Reserved. 164D-0919