

AIRFLOW ADDENDUM FOR *RC120D-16C FURNACES

| Model Number | Heating Input (Btuh) | Motor Speed | Motor HP | External Static Pressure (Inches Water Column) | | | | | | | | | | | | | | | |
|------------------------------|----------------------|-------------|----------|--|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| | | | | 0.1 | | 0.2 | | 0.3 | | 0.4 | | 0.5 | | 0.6 | | 0.7 | | 0.8 | |
| | | | | CFM | Rise | CFM | Rise | CFM | Rise | CFM | Rise | CFM | Rise | CFM | Rise | CFM | Rise | CFM | Rise |
| *RC120D-16C *GC1RC120D16C | 120,000 | High* | 3/4 | 2185 | - | 2130 | - | 2075 | 49 | 2010 | 50 | 1945 | 52 | 1865 | 55 | 1785 | 57 | 1690 | 60 |
| | | Med-High** | | 1945 | 53 | 1915 | 54 | 1865 | 55 | 1815 | 56 | 1760 | 58 | 1690 | 60 | 1615 | 63 | 1525 | 67 |
| | | Med-Low | | 1700 | 60 | 1645 | 62 | 1615 | 63 | 1600 | 64 | 1570 | 66 | 1490 | 68 | 1425 | 71 | 1345 | 76 |
| | | Low | | 1230 | - | 1225 | - | 1200 | - | 1160 | - | 1145 | - | 1115 | - | 1080 | - | 1050 | - |

* Factory Set Cooling Speed
 ** Factory Set Heating Speed
 - Not Recommended

Notes: 1. Airflow rates of 1800 CFM or more require two return air connections. Data is for operation with filter(s).
 2. Temperature rises in the table are approximate. Actual temperature rises may vary.
 3. Temperature rises and airflows for external static pressures greater than 0.5 are for reference only. These conditions are not recommended.

